

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 10/21/2015

1 Identification

- **Product identifier**
- **Trade name: Polyester TGIC**
- **Article number:**
UN-707770XXXXXX, UN-703700XXXXXX, UN-703730XXXXXX, UN-707370XXXXXX, UN-707375XXXXXX, UN-707562XXXXXX, UN-707563XXXXXX, UN-707670XXXXXX, UN-707775XXXXXX
- **Application of the substance / the mixture**
Coating powder for professional use
Powder application by electrostatic spraying
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Univercol
Hamelacha st. 6
Netanya industrial zone
P.O. Box 8161
Netanya 42505
ISRAEL
- **Information department:**
Product safety department: Israel Michal 054-2341336, Ira Yoavi 054-5660537
- **Emergency telephone number:** During normal opening times: +972-9-8637555

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.
Carc. 2 H351 Suspected of causing cancer.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05 GHS07 GHS08

Safety Data Sheet
acc. to OSHA HCS



Printing date 10/21/2015

Reviewed on 10/21/2015

Trade name: Polyester TGIC

(Contd. of page 1)

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione
Titanium Dioxide
- **Hazard statements**
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H340 May cause genetic defects.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P272 Contaminated work clothing must not be allowed out of the workplace.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P302+P352 IF ON SKIN: Wash with plenty of water.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**
 Health = 2
Fire = 0
Reactivity = 0
- **HMIS-ratings (scale 0 - 4)**
 HEALTH *1 Health = *1
FIRE 0 Fire = 0
REACTIVITY 0 Reactivity = 0
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 10/21/2015

Trade name: Polyester TGIC

(Contd. of page 2)

· Dangerous components:		
7727-43-7	barium sulphate, natural	10-<25%
13463-67-7	Titanium Dioxide	10-<25%
2451-62-9	1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	2.5-<10%
112926-00-8	Precipitated silica (Silica-Amorphous)	0.1-≤2.5%
21645-51-2	aluminium hydroxide	0.1-≤2.5%
1344-28-1	aluminium oxide	0.1-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Foam, carbon dioxide blanket, dry powder, fine water spray.
For burning cartons, dry powder and foam are preferred extinguishing agents.
- **For safety reasons unsuitable extinguishing agents:**
Strong water jets or inert gas under high pressure could cause burning powder to swirl up and prevent effective fire-fighting.
- **Special hazards arising from the substance or mixture**
Thick, black smoke is emitted when burning which should not be inhaled.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Avoid dust formation and keep away from ignition sources. Do not inhale dust.
- **Environmental precautions:**
Do not allow to enter drains. In case of pollution of rivers, lakes or drains, notify the appropriate authorities.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 10/21/2015

Trade name: Polyester TGIC

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**
Clean up spilled dry material with an ex-proof vacuum cleaner or carefully with a broom. Dispose of spilled material according to local regulations.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Do not eat, drink or smoke while working. Refer to section 8 concerning personal precaution.
- **Information about protection against explosions and fires:**
Keep away from all sources of ignition, heat and open fire. Dust can form an explosive mixture with air. Take precautions against build-up of electrostatic charge: Use earthened equipment when transferring powder between vessels. Wear antistatic footwear with conductive soles. The floor must be electrically conductive. Use non-sparking application equipment. Check the earthing of the spray booth periodically.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Smoking prohibited. Keep opened cartons properly closed carefully.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store at between 15 and 25°C in a dry and well ventilated place. Protect from heat and direct sunlight.
Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7727-43-7 barium sulphate, natural

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 5* mg/m³
*inhalable fraction; E

2451-62-9 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione

TLV Long-term value: 0.05 mg/m³

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 10/21/2015

Trade name: Polyester TGIC

(Contd. of page 4)

112926-00-8 Precipitated silica (Silica-Amorphous)

PEL	20mppcf or 80mg/m ³ /%SiO ₂
REL	Long-term value: 6 mg/m ³ See Pocket Guide App. C
TLV	TLV withdrawn

21645-51-2 aluminium hydroxide

REL	Long-term value: 2 mg/m ³ as Al
TLV	Long-term value: 1* mg/m ³ as Al; *as respirable fraction

1344-28-1 aluminium oxide

PEL	Long-term value: 15*, 15** mg/m ³ *Total dust; ** Respirable fraction
REL	Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV	Long-term value: 1* mg/m ³ as Al; *as respirable fraction

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
If dust concentration is greater than the TLV, a suitable dust mask must be worn.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 10/21/2015

Trade name: Polyester TGIC

(Contd. of page 5)

- **Eye protection:**
If a high level of dust release is expected, a protective goggles should be worn.



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Powder
· Color:	Various colors
· Odor:	Odorless
· Odour threshold:	Not determined.

· **pH-value:** Not applicable.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	999 °C (1830 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:** 0 °C (32 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Air-dust mixtures may be explosive.

· **Explosion limits:**

· Lower:	0,0 Vol % 20-70* mg/m ³
· Upper:	0,0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 0,1 hPa

· **Density at 20 °C (68 °F):** 1.70573 g/cm³ (14.234 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not applicable.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with**

· **Water:** Insoluble.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· Dynamic:	Not applicable.
· Kinematic:	Not applicable.

· **Solvent content:**

· **Organic solvents:** 0.0 %

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 10/21/2015

Trade name: Polyester TGIC

(Contd. of page 6)

Solids content: 100.0 %
Other information: * A value of 10 mg/m³ must not be exceeded during system operation.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Stable under the recommended storage and handling conditions, (see Section 7).
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

Oral	LD50	2500 mg/kg
Inhalative	LC50/4 h	9.66 mg/l

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
The product can cause inheritable damage.

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
112926-00-8	Precipitated silica (Silica-Amorphous)	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 10/21/2015

Trade name: Polyester TGIC

(Contd. of page 7)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | Void |
| · DOT, ADR, ADN, IMDG, IATA | Void |
| · UN proper shipping name | Void |
| · DOT, ADR, ADN, IMDG, IATA | Void |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | Void |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | Void |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 10/21/2015

Trade name: Polyester TGIC

(Contd. of page 8)

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

7727-43-7 barium sulphate, natural

1344-28-1 aluminium oxide

· **TSCA (Toxic Substances Control Act):**

7727-43-7 barium sulphate, natural

2451-62-9 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione

21645-51-2 aluminium hydroxide

1344-28-1 aluminium oxide

119-53-9 benzoin

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

· **TLV (Threshold Limit Value established by ACGIH)**

1344-28-1 aluminium oxide

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione
Titanium Dioxide

· **Hazard statements**

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 10/21/2015

Trade name: Polyester TGIC

(Contd. of page 9)

H340 May cause genetic defects.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department

· **Contact:** Mrs. Ira Yoavi iray@nirlat.com

· **Date of preparation / last revision** 10/21/2015 / 2

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Muta. 1B: Germ cell mutagenicity, Hazard Category 1B

Carc. 2: Carcinogenicity, Hazard Category 2

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2